S-Series S-15T

STYLISH DESIGN

AG Neovo S-Series Displays

Made for those who
want a stylish award winning display

Elegant & Rugged Design

Smart exterior with exceptional strength

Ease Of Use

Access information directly via the touch enabled display

Life Performance

Impact resistant touch screen offers longer usage period

Picture-In-Picture

Simultaneous computer display and video signal playback

Desk/Arm/Wall Flexibility

VESA Compatible LCD display arm or wall mount kit both available

Features
Touch Screen Technology
15" TFT Active Matrix Screen
1024 x 768 Resolution
Foldable Small Footprint Stand
Picture-In-Picture

AG neovo

A Different Class Of Display

S-Series Displays

Touch Panel
Instantly access data via the touch sensitive display panel.

Wide Viewing Angle
Wide angle viewing technology offers greater viewing clarity even when the display is seen from different angles.

Picture-In-Picture
Watch computer display and DVD, VCR or other video simulataneously.

Auto-Adjustment
Automatically adjusts screen settings for an optimal image, without changing settings manually.

OSD
On-Screen Display (OSD) makes adjusting the display settings quick and convenient.

Total Flat Display
A completely flat display, with absolutely no curvature, generates a truer and less distorted view.

LCD Display Arm
Advanced gas-spring suspension guarantees smooth stable operation, and flexibility of use.

Wall Mount Kit
Mount the LCD display on the wall to save even more valuable desktop space.

Security Lock
Increase security by anchoring the LCD display to an immovable object. Compatible with Kensington® security locks.

Specifications

		S-15T
Panel	Panel Type	TFT LCD
	Panel Size	15.0" (381mm)
	Max. Resolution	XGA 1024 x 768
	Pixel Pitch	0.297mm
	Brightness	250cd/m² (Typical)
	Contrast Ratio	500:1 (Typical)
	Surface Treatments	Hard Coating (2H) & Anti-glare treatment
	Viewing Angle (H/V)	170°/170° (Minimum)
	Display Color	16.7M
	Response Time	15ms /10ms (Typical)
	Wide Viewing Angle	Yes
	Frequency	Horizontal: 30kHz - 60kHz Vertical: 50Hz - 75Hz
	Max. Pixel Clock	80MHz
Inputs	Analog	15-Pin Mini D-Sub
	Video	4-Pin Mini Din S-Video CVBS Jack
Connector	Power	3-Pin AC Plug
Touch Screen	Technology	SAW (Surface Acoustic Wave)
	Glass Panel Transmission	>90%
	Positional Accuracy	<0.08" (2mm) Deviation error
	Resolution	4096 x 4096
	Active Force	2 - 3 ounces (55 - 85g)
	Life Performance	50 million touches in one location
Tilt/Swivel	Tilt Angle / Swivel	10° (Tilt)
Mounting	VESA FPMPMI	Yes (75 mm)
Dimensions	Net (W x H x D)	386 x 360 x 169mm (17.0" x 16.0" x 6.7")
	Packing (W x H x D)	475 x 480 x 210mm (48.7" x 18.9" x 8.3")
Weight	Net Weight	5.5Kg (12.1lb)
	Gross Weight	7.5Kg (16.5lb)
Regulation Approval	Safety & EMI	FCC, UL/CUL, EPA, TUV/BAURT, CE, NORDIC, TCO95, NUTEK, BSMI, VCCI, CCC, CB
	VESA	DDC1/2B, DPMS
Power	Power AC Consumption	100~240V, 50~60Hz < 48W (On), < 5W (Stand-by) < 5W (Off)

All specifications are subject to change without prior notice. © 2003 Associated Industries China Inc.
The name AG Neovo is a trademark of AIC. All other trademarks are the property of their respective owners.

Optional Accessories

WIRELESS R/F KEYBOARD & MOUSE

LCD DISPLAY ARM

TV TUNER FRAME

WALL MOUNT KIT

AG neovo
A Different Class Of Display

DM Code: MKT-S5TE-0303